



CEM-SPRAY Spray Texture

SPRAY TEXTURE SYSTEMS

Description

CEM-SPRAY Spray Texture is a ready-mix powder compound used in the application of interior surfaces. It can be applied to the ceilings, walls, wooden furniture etc. by a hopper gun or spray plastering machines. A wide range of texture patterns can be created using a roller, brush, spray plastering machine or a hopper spray gun.

Areas of Application

- Concrete Substrates.
- Masonry surfaces.
- Plastered walls.
- Dry wall.
- Cement Boards.
- Interior Surfaces.

Features & Benefits

- Easy Mixing.
- Spreads easily.
- Non aggregated texture.
- Excellent adhesion over a wide variety of porous surfaces, concrete, and all types of masonry surfaces.
- Developed for different texture patterns.
- Prevents common undesired effects like craters, lumps, pin holes.

Method of Application

1 Surface Preparation

- The substrate needs to be structurally sound and free from grease, oil, wax, wall paper glue, dust and loose particles.
- Remove the loose particles and fill the cracks if any.
- The wall shall be filled so that a seamless, smooth and flat surface is achieved.

2 Mixing

- Add 25 kg bag of CEM-SPRAY Spray Texture to 15 liters of water. Mix it in a clean container using a hand operated mechanical mixer to a heavy but lump-free, homogeneous and workable consistency is obtained.
- Consistency can be adjusted by addition of water.
- Always mix the required quantity, which can be consumed within 60 minutes pot life.

3 Application

- Surfaces such as joint treated must be smooth, clean and dry.
- First apply a coat of sealing primer and allow the primer to dry thoroughly and maintain adequate drying conditions after application.
- Sealing primer is required to avoid sagging of gypsum board and discoloration or difference in sheen of ceiling and walls.
- Pour the homogeneous mix in the hopper of the spray gun and spray it on the required surface.
- Adequate ventilation should be provided to eliminate the excess moisture.



CEM-SPRAY Spray Texture

SPRAY TEXTURE SYSTEMS

1 Application of Primer and Paint

- Clean the surface using a soft brush and remove all the dust and loose particles.
- Start the application of single coat of primer.
- Apply two coats of paint of the desired shade (Let the surface dry between coats).

2 Sealer Application

- For Matt Finish: Do not apply sealer coat.
- For Glossy Finish: Apply a coat of sealer with roller.

Precautions & Limitations

- For laying tiles on floor, Surface should be sufficiently hard & good condition.
- It is recommended for interior application only.
- Always add powder to water & never add water to powder.
- Do not add excess water than recommended.
- For spraying on walls and ceiling, the surface should be sufficiently hard & good condition.
- It is not considered as a finished surface.
- Sealer coat is required after texturing to avoid difference in sheen on wall and ceiling surface.

Technical Information

S.No.	Properties	Results
1	Appearance	Off White
2	Textures	Knockdown/Spatter/Acoustic/Orange Peel

Coverage

100 Sft/25 Kg Bag

Packaging

25 Kg

Shelf Life

12 months from date of production.

Storage

Store in a sealed packaging in cool dry condition in a room temperature



Head Office: 2/C, Nasibullah Compound, Kurla-Kalina Road, Kurla (W), Mumbai 400070.
Contact : 9987279164 | 9987279169 Email : info@cementric.com

Disclaimer: The product information & application details given by the company & its agents has been provided in good faith & meant to serve only as a general guideline during usage. Users are advised to carry out tests & take trials to ensure on the suitability of products meeting their requirement prior to full scale usage of our products. Since the correct identification of the problems, quality of other materials used and on-site workmanship are factors beyond our control, there are no expressed or implied guarantee / warranty as to the results obtained.



CEM-SPRAY Spray Texture

SPRAY TEXTURE SYSTEMS

Health & Safety Precautions

- Dust or mist may cause irritation to eyes, skin, nose, throat or respiratory tract.
- Use of a mask, eye protective gear is recommended during spray texture application.
- The area should be fully ventilated or provide sufficient local ventilation to avoid breathing of dust.
- Any eye contamination should be washed immediately with plenty of clean water and medical advice sought.
- CEM-SPRAY is inflammable.

Other Products Available

Tile Fix Mortar Tile Grouts Block Joining Mortar Readymix Plaster Ruff Tuff Textures Industrial Grade Hardener
Decorative Colour Hardener Neutral & Colour Release Sealers Epoxy Resins Concrete Admixtures Paints & Allied
Products.



Head Office: 2/C, Nasibullah Compound, Kurla-Kalina Road, Kurla (W), Mumbai 400070.
Contact : 9987279164 | 9987279169 **Email :** info@cementric.com

Disclaimer: The product information & application details given by the company & its agents has been provided in good faith & meant to serve only as a general guideline during usage. Users are advised to carry out tests & take trials to ensure on the suitability of products meeting their requirement prior to full scale usage of our products. Since the correct identification of the problems, quality of other materials used and on-site workmanship are factors beyond our control, there are no expressed or implied guarantee / warranty as to the results obtained.